



GE APPLIANCES
a Haier company

CustomerNet

GE Zoneline® UltimateV12™ Heat Pump Single Package Vertical Air Conditioner with Makeup Air, 230/208 Volt Model# AZ9VH12DBM



- Insta-Platform™ - Eliminates the need for on-site customized platform construction saving time and money
- Self-Contained Drainage System - Easy installation allows for simple chassis removal while leaving plumbing completely intact
- Fast-Connect Plumbing - Allows preliminary plumbing to be installed outside the closet and prior to installing the chassis
- Self-Aligning Lock-in-Place System - The Insta-Platform and the VTAC are self-aligning with a lock-in-place system ensuring the unit is engaging with the plenum gasket
- Quick-Install Plenum - Plenum is easily installed from the interior of building, without the need for exterior building access. Caulking is required. It conveniently expands from 8" to 15" for a custom fit
- Onboard Diagnostics - Electronic controls give clear and fast diagnostics data and fault codes, for fast and easy resolution
- SmartHQ™ WiFi capability - Optional SmartHQ module* gives property managers the ability to monitor multiple units remotely, enhancing guests' experience. Learn more at smarthqsolutions.com/management (*SmartHQ module part number PBX23W00Y0 or PBX23W00Y1.)
- Ultra-Quiet - Delivers quiet cooling power with a smooth sound for a good night's sleep
- Reverse Cycle Defrost - The variable speed compressor and advanced defrost capability allow for the best heat pump operation down to 0° F

FEATURES

Fan Speed Selections	3 Cooling
Sensible Heat Ratio	75%
Product Type	Vertical Air Conditioners
Refrigerant Type	R410A
Remote Thermostat	RAK190V
Makeup Air	Yes
Heat Sentinel	Yes
VTAC Features	Anti-Corrosion Design Auto Compressor Random Restart Automatic Emergency Heat Automatic Indoor Frost Control Boost Heat Chassis Design with Perfect Fit to Insta-Platform™ and Quick-Install Plenum (sold separately) Fast-Connect Plumbing Freeze Sentinel Heat Pump with Resistance Heat Backup Heat Sentinel Onboard Electronic Error Diagnostics Quick Heat Recovery Reverse Cycle Defrost Self-Aligning, Lock In Place Platform System Self-Contained Drainage System SmartHQ WiFi Capability Thermostat Quick Disconnect Ultra-Quiet
Heat Pump	Yes
Power Connection Kit	RAK3XXD Series
Freeze Sentinel	Yes
Corrosion Treated	Yes
Central Desk Control Compatibility	Yes
Rotary Compressor	Yes
Heating - Reverse Cycle - COP	3.6
Heating System	Heat Pump

- Anti-Corrosion Design/Premium Guard Seacoast Protection - Exclusive rust-proof basepan and bulkhead provide another level of corrosion protection to ensure lasting performance in challenging environments
- Inverter Technology - Variable speed operation provides an advantage with shorter recovery time, improved efficiency, sound quality and dehumidification. Consistent room temperature allows for total room comfort
- Adjustable Speed Makeup Air - Makeup air and customizable variable speed fan technology provide the precise airflow for specific applications. For energy savings, makeup air delivery can be cycled based on occupancy, using a compatible occupancy detecting thermostat. Optional MERV 13 filtration available
- Designed & Assembled in America

Have more questions? Please contact 1-800-626-2000



GE APPLIANCES
a Haier company

CustomerNet

GE Zoneline® UltimateV12™ Heat Pump Single Package Vertical Air Conditioner with Makeup Air, 230/208 Volt Model# AZ9VH12DBM

APPROXIMATE DIMENSIONS(HxDxW)

- 31 7/8H x 23 5/8W x 24 1/8D

CAPACITY

- Cooling BTUH (MAX) - 12100.00Btu
- CFM Indoor Fan Low - 376
- CFM Indoor Fan Medium - 417
- Cooling EER (BTUH / Watt) - 11.6
- Heating - Reverse Cycle - BTUH - 11400
- Dehumidification (pts./hr.) - 3.16

APPEARANCE

- Color Appearance - Gray

WEIGHTS & DIMENSIONS

- Overall Width (in) - 23 5/8in
- Approximate Shipping Weight (lb) - 150lb
- Overall Height (in) - 31 7/8in
- Overall Depth (in) - 24 1/8in
- Net Weight (lb) - 137lb

POWER / RATINGS

- Heating - Reverse Cycle - Watts - 925
- Cooling - Amperes - 4.7
- Cooling - Watts - 1040
- Heating - Reverse Cycle - Amps - 4.3
- Voltage (MIN) - 208V
- Voltage (MAX) - 230.000000V

ACCESSORIES

- Accessories Required for Installation - Outdoor Grille - RAVAL3
Plenum - RAVWPT15 or RAVTRANS2, 3, 4
RAVDPLAT
Return Air Grille - RAVRG4, RAVRG2
Wall Thermostat - RAK149F2, RAK149P2, RAK180W1

WARRANTY

- Warranty Notes - See written warranty for full details
- Labor Warranty - Limited 1-year entire appliance
Limited 5-year sealed refrigerating system
- Parts Warranty - Limited 1-year entire appliance
Limited 5-year parts
Limited 5-year sealed refrigerating system

CERTIFICATIONS

- Claims & Certifications - California Prop 65

